



**RECESSED SPOTLIGHT
4.0021**

EXTERIOR

IP67



- › Orientation light for standard mounting boxes
- › Up to 165 lumen light intensity
- › Round or square aperture





4.0021 | 4.0020 | RECESSED SPOTLIGHT

FOR ILLUMINATION AND ORIENTATION FOR FACADES, TERRACE, WAYS AND GARDENS.



- Protection system IP67
- cover made of stainless steel 316Ti
- Housing made of anodised aluminium
- Round or square attachment cover, height 3mm
- Toughened safety glass (ESG) – withstands loads of up to 650 kg
- ...
- POW-LED cold white, warm white, neutral white
- POW-LED colored
- operating mode: constant current
- ...
- For floor installation with a plastic installation container
- Supplied with plastic installation container and 3 m of connecting cable




RECESSED SPOTLIGHT 4.0021

EXTERIOR


IP67



R



S



R	S									
Article number	Article number	Lamps	Lumen	Light colour	Wattage	Current	Temperature	Radiation angle	Cable, installs	[V]
RADATION ANGLE 30° (MEDIUM)										
4.0021.20.01	4.0021.40.01	1 POW-LED	165 lm	6000K cold white	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	V14
4.0021.20.02	4.0021.40.02	1 POW-LED	135 lm	3000K warm white	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	
4.0021.20.03	4.0021.40.03	1 POW-LED	155 lm	4500K neutral white	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	
4.0021.20.04	4.0021.40.04	1 POW-LED		yellow	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	
4.0021.20.05	4.0021.40.05	1 POW-LED		red	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	
4.0021.20.06	4.0021.40.06	1 POW-LED		blue	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	
4.0021.20.07	4.0021.40.07	1 POW-LED		green	total 2 W	CC 350 mA	<40°C	30° medium	UW, 2x0,5 qmm	
RADATION ANGLE HOMOGEN DIFFUS										
4.0020.20.01	4.0020.40.01	1 POW-LED	165 lm	6000K cold white	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	
4.0020.20.02	4.0020.40.02	1 POW-LED	135 lm	3000K warm white	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	
4.0020.20.03	4.0020.40.03	1 POW-LED	155 lm	4500K neutral white	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	
4.0020.20.04	4.0020.40.04	1 POW-LED		yellow	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	
4.0020.20.05	4.0020.40.05	1 POW-LED		red	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	
4.0020.20.06	4.0020.40.06	1 POW-LED		blue	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	
4.0020.20.07	4.0020.40.07	1 POW-LED		green	total 2 W	CC 350 mA	<40°C	homogen diffus	UW, 2x0,5 qmm	



RECESSED SPOTLIGHT 4.0021



IP67

EXTERIOR



< Project
 Australien War Memorial, Australia
 Planner: Form & Light, Sydney;
 Photo: www.kevinhawkinsphotography.com

Power supplies Technical details see from page 234.

5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20

Constant Current power supply, max 3 spotlights

Constant Current power supply, max 6 spotlights

Constant Current power supply, max 12 spotlights

5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20
5.0635.65.03	5.0635.65.10	5.0635.65.20

Constant Current power supply, max 3 spotlights

Constant Current power supply, max 6 spotlights

Constant Current power supply, max 12 spotlights

NOTE



POW-LED, series-connected



Glass surface temperature below 40° (Cool Contact)

OPTIONS

Possible beam angle

